

# Delock Thunderbolt™ 3 (20 Gb/s) USB-C™ cable male > male passive 2.0 m 3 A black

## Description

This Thunderbolt™ 3 cable by Delock is universally applicable and combines all the advantages of the Thunderbolt™ 3 interface. It allows the connection of different devices such as external enclosures, monitors, card readers and docking stations via a Thunderbolt™ 3 port of a PC or laptop. The cable provides data transfer rates of up to 20 Gb/s and supports USB, Displayport, PCI Express as well as Ethernet data transfer. The connection of a 5K or a 4K Displayport monitor is possible, as is the connection of USB 3.1 Gen 1 devices. Furthermore the cable enables the power supply of connected devices with up to 60 W.



up to  
**20**  
Gb/s



ca. 2 m

## Specification

- Connector:
  - 1 x Thunderbolt™ 3 USB Type-C™ 24 pin male >
  - 1 x Thunderbolt™ 3 USB Type-C™ 24 pin male
- Chipset: Cypress E-Marker
- Cable gauge:
  - 32 + 34 AWG data line
  - 24 + 34 AWG power line
- Cable diameter: ca. 4.6 mm
- Conductors: 8 x coaxial for SuperSpeed USB, 1 x Twisted Pair for USB 2.0
- Gold-plated connector
- Triple shielded cable
- Data transfer rate:
  - Thunderbolt™ 3 up to 20 Gb/s
  - Displayport 1.2a up to 21.6 Gb/s
  - SuperSpeed USB up to 5 Gb/s
  - Thunderbolt™ Networking up to 10 Gb/s (Peer-To-Peer)
- Display resolution up to:
  - 1 x 5120 x 2880 30 Bit @ 60 Hz or
  - 1 x 4096 x 2160 30 Bit @ 60 Hz
  - (depending on the system and the connected hardware)
- Supports data and video on a single cable
- Supports PCI Express 3.0 protocol (4 lanes)
- Supports Displayport 1.2a protocol (8 lanes, HBR2 and MST)
- Daisy Chain up to 6 Thunderbolt™ devices (cascadable)
- Dual channel, bi-directional data transfer
- Power supply via USB Power Delivery up to 60 W (20 V / 3 A)
- Power supply for Thunderbolt™ 3 devices with bus power (max. 15 W)
- Colour: black
- Length without connector: ca. 2.0 m

## System requirements

- PC or laptop with a free Thunderbolt™ 3 port

## Package content


- Thunderbolt™ cable

Item no. 84847


EAN: 4043619848478

Country of origin: China

Package: Retail Box



Images



General	
Specification:	<b>standard</b> Thunderbolt™ 3
Interface	
connector 1:	<b>standard</b> 1 x Thunderbolt™ 3 USB Type-C™ 24 pin male
connector 2:	<b>standard</b> 1 x Thunderbolt™ 3 USB Type-C™ 24 pin male
Technical characteristics	
Chipset:	<b>standard</b> Cypress E-Marker
Data transfer rate:	<b>standard</b> Thunderbolt™ 3 up to 20 Gb/s Displayport 1.2a up to 21.6 Gb/s USB 3.1 Gen 1 up to 5 Gb/s Gigabit Ethernet up to 10 Gb/s
Maximum screen resolution:	<b>standard</b> 5120 x 2880 @ 60 Hz 4096 x 2160 @ 60 Hz
Maximum load:	<b>standard</b> 100 W 15 W (Bus Power)
Maximum current:	<b>standard</b> 5 A
Physical characteristics	
Cable diameter:	<b>standard</b> 4.6 mm
Pin finishing:	<b>standard</b> gold-plated
Conductors:	<b>standard</b> 1 x Twisted Pair 8 x coaxial
Conductor gauge:	<b>standard</b> 32 AWG data line 34 AWG data line 24 AWG power line 34 AWG power line
Shielding:	<b>standard</b> triple
Length:	<b>standard</b> 2 m
Colour:	<b>standard</b> black