



NOTES:

1.ELECTRICAL PROPERTIES:

- 1.1 100% OPEN AND SHORT TEST
- 1.2 CONDUCTOR RESISTANCE: 5 OHMS
- 1.3 INSULATION RESISTANCE: 10 MEGOHMS
- 1.4 HI-POT: DC300V/0.01S
- 1.5 100% HDTV, BLUE PAY DVD TEST(1080P: 7M); (1080I: 10M,15M)
- 1.6 ALL CABLE PROCESS SHOULD BE CONTROLLED BY ATC TEST DEVICE.

2. ALL MATERIAL BE RoHS COMPLIANT.

⑧	TAG	1PCS	DELTACO TAG
⑦	CORE MOLD	2PCS	BLACK PVC
⑥	CORE	2PCS	OD*ID*L: 17.5*12*28.5mm
⑤	SCREW	2PCS	#4-40 UNC, HOOD MOLDED: BLACK PVC
④	DVI HOOD	2PCS	BLACK PVC
③	DVI(24+5)M	1PCS	GOLD PLATED SHEL
②	DVI(24+5)M	1PCS	GOLD PLATED SHELL
①	CABLE	1PCS	(30AWG*1P+D+FAM)*7+(28AWG+S+FAM)*3+28AWG*1P+28AWG*5C+AEB OD:9.5mm BLACK PVC JACKET
NO.	PARTS NAME	Q'TY	SPECIFICATION

APPROVED	CHECKED	DRAWN	CUSTOMER:	
			ITEM NO.	DVI-625A
			DRAW NO.	
			UNIT	mm
			SCALE	NONE

DESCRIPTION:

DVI(24+5)MALE/MALE

