

Ekspansionsbeholder for brugsvand.

Fordele

- Påfyldt nitrogengas sikrer længere opretholdelse af fortryk.

Tekniske informationer

- Min./ maks.temperatur: -10 / 100 °C (på membranen).
- Fortryk: 3.5 bar.
- Maks. driftstryk 10 bar
- Farve: Grå (RAL 9006).



Beskrivelse	Airfix P DHW exp.ves. 3/3,5[10bar]	
Flamco nr.	24851	
GTIN	08712874248519	
Type	<u>Airfix P 2 - 300</u>	
Vand- indhold [l]	3	
Pre- charge [bar]	3,5	
Dimensioner	Ø [mm]	170
	H. [mm]	240
Tilslutning	G $\frac{3}{4}$ " M	
Membran	Butyl	
Vægt [kg]	1,5	



Generel data

Etim gruppe	Pressure increase/decrease
Etim klasse	Membrane pressure expansion vessel
Produkt navn	Airfix P DHW exp.ves. 3/3,5[10bar]
Brand	FLAMCO
Udførelse	Sanitary Welded [10bar] 2 - 80 L
Artikelnummer	24851
GTIN	08712874248519

Detaljer

Suitable for central heating	No
End pressure	10 Bar
Suitable for cooling	No
Suitable for tap water	Yes
Suitable for tap water	Yes
Suitable for solar collector circuit	No
Volume	3 Litre
Pre-pressure	3.5 Bar
On base, vertical	Yes
On base, horizontal	No
Max. Arbejdstryk	3 Bar
With fixed wall support	No
Vertical positioning	Yes
Max. medium temperature (continuous)	70 Degrees celsius
Horizontal positioning	No
With legs	No
With exchangeable membrane	Yes
Nominal diameter expansion connection	3/4 inch (20)
Outer pipe diameter, expansion connection	26.5 Millimetre
Tilslutning	External thread cylindrical BSPP-G (ISO 228-1)
With vessel manifold	No
With drain	No
Diameter	170 Millimetre
Højde	240 Millimetre
Med manometer	No
Med sikkerhedsventil	No
Med monteringsmateriale	No

Find flere oplysninger online:[Monterings- og driftsvejledning](#)[Certifikat ACS P 2-12](#)[Certifikat ACS P 16-1000](#)[WRAS Certifikat](#)[Airfix P 2-5 ADSK](#)[Airfix P 2-5 DWG](#)[Airfix P 2-5 IPT](#)[Airfix P 2-5 STEP](#)[Katalog i PDF](#)

Tonsbakken 16-18
DK-2740, Skovlunde - dk

T +45 44 94 02 07
E dk.info@aalberts-hfc.com
I flamcogroup.com/dk