



Halogen Clickline G9



Halogen MV Click 18W G9 230V CL 1CT

Ideal solution for small decorative luminaires. UV-block glass and safety fuse allow usage without cover glass. The compact Clickline gives crisp white light over a long lifetime.

Product data


General information	
Cap-Base	G9 [G9]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal Lifetime (Nom)	2000 h
Switching Cycle	8000X
Rated Lifetime (Hours)	2000 h
Flux measurement reference	Sphere
Light technical	
Luminous Flux (Nom)	195 lm
Luminous Flux (Rated) (Nom)	204 lm
Chromaticity Coordinate X (Nom)	0.452
Chromaticity Coordinate Y (Nom)	0.409
Correlated Color Temperature (Nom)	2800 K
Luminous Efficacy (rated) (Nom)	11.1 lm/W
Color Rendering Index (Nom)	100
LLMF at End of Nominal Lifetime (Min)	80 %
Operating and electrical	
Power (Nom)	19 W
Lamp Current (Nom)	0.08 A
Starting Time (Nom)	0.0 s
Warm Up Time to 60% Light (Nom)	instant full light
Power Factor (Nom)	1

Voltage (Nom)	230 V
Controls and dimming	
Dimmable	Yes
Mechanical and housing	
Bulb Finish	Clear
Bulb Shape	T13 [T 13 mm]
Approval and application	
Energy Efficiency Class	G
Energy Consumption kWh/1000 h	19 kWh
EPREL Registration Number	423243
Luminaire design requirements	
Bulb Temperature (Max)	950 °C
Pinch Temperature (Max)	350 °C
Product data	
Full product code	872790089577300
Order product name	Halogen MV Click 18W G9 230V CL 1CT
EAN/UPC - Product	8727900895773
Order code	925697744201
Numerator - Quantity Per Pack	1

Halogen Clickline G9

Numerator - Packs per outer box	100
Material Nr. (12NC)	925697744201
Net Weight (Piece)	3.300 g

Dimensional drawing



Halogen MV Click 18W G9 230V CL 1CT

Product	D (max)	L	C (max)
Halogen MV Click 18W G9 230V CL 1CT	13 mm	21.7 mm	45 mm

