



PIN OUT

P1	P2	Color
1	1	RED
6	6	
2	2	GREEN
7	7	
3	3	BLUE
8	8	
4	4	RED
5	5	YELLOW
9	9	ORANGE
10	10	PURPLE
11	11	GRAY
12	12	BLUE
13	13	GREEN
14	14	BLACK
15	15	BROWN
SHELL	DRAIN WIRE	SHELL

- NOTES:
1. ELECTRICAL PROPERTIES:
    - 1.1 100% OPEN AND SHORT TEST
    - 1.2 CONDUCTOR RESISTANCE: 5 OHMS
    - 1.3 INSULATION RESISTANCE: 10 MEGOHMS
    - 1.4 HI-POT: DC300V/0.01S
  2. ALL MATERIAL BE RoHS COMPLIANT.

NO.	PARTS NAME	Q'TY	SPECIFICATION
⑧	TAG	1PCS	DELTACO TAG
⑦	CORE MOLD	2PCS	GRAY PVC
⑥	CORE	2PCS	OD*ID*L: 17.5*10.5*28.5mm
⑤	SCREW	2PCS	#4-40 UNC, 4*46mm HOOD MOLDED: BULE PVC
④	HOOD MOLD	2PCS	BULE PVC
③	INNER MOLD	2PCS	PE
②	HDB 15P M	2PCS	NICKIEL PLATED SHELL
①	CABLE	1PCS	UL20276(28AWG*1C+S+PVC)*3+24AWG*9C+AEB OD:9.0mm GRAY PVC JACKET

APPROVED	CHECKED	DRAWN	CUSTOMER:
			ITEM NO. RGB-2A
			DRAW NO.
			UNIT mm
			SCALE NONE

DESCRIPTION:

HDB 15/M-HDB 15/M

